


DEDUST 2 Dust collector for dust recovery and disposal

AIR FILTRATION SOLUTIONS



- ✓ 100% steel construction.
- ✓ Easy-to-empty detachable container.
- ✓ Large antistatic filter surface
- ✓ Possibility of localised vacuuming thanks to an optional extraction arm
- ✓ Designed for vacuuming fine airborne dust

Suction unit

Voltage	V - Hz	400 - 50 3~
Power	kW	1,5
Max waterlift	mmH2O	142 - 115
Max air flow	m3/h	2400 - 1350
Suction inlet	mm	2 x 150 1 x 200
Noise level (EN ISO 3744)	dB(A)	70

Filtering Unit

Primary filter		Cartridge
Total filtering surface area	cm ²	200.000
Numero di cartucce		2
Ø filter		325
Material - Efficiency	IEC 60335-2-69	Poliestere ANT M
Cleaning system		Automatico PN

Collection unit

Powder capacity	lt	30
-----------------	----	----

Encumbrances

Dimensions	cm	115 x 82 x 170h
Weight	kg	235

APPLICATIONS: Mechanical industry Sandblasting Wood and plastic  Food, chemical and pharmaceutical industry



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

DEDUST 2 Dust collector for dust recovery and disposal

AIR FILTRATION SOLUTIONS

SUCTION UNIT

The suction unit is an electric fan that provides the system with a high air flow.

FILTERING UNIT

The antistatic polyester stellar filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

The cartridges are automatically cleaned by an automatic, timed and alternate pneumatic reverse air cleaning system. The air supply is provided by a compressor that can be installed (on request) on the rear fairing.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

- ✓ Absolute hepa filter h13 efficiency 99.95%
- ✓ Techflex extraction arm d200
- ✓ Techflex extraction arm d150
- ✓ Spark trap kit