

Oilvac 500

INDUSTRIAL VACUUM CLEANERS



- ✓ Designed for complete cleaning of CNC machines, all in one vacuum.

Suction unit

| | | |
|---------------------------|--------|-------------|
| Voltage | V - Hz | 400 - 50 3~ |
| Power | kW | 4 |
| Max waterlift | mmH2O | 3.200 |
| Continuous water lift | mmH2O | 2.400 |
| Max air flow | m3/h | 420 |
| Relief valve | | Integrated |
| Noise level (EN ISO 3744) | dB(A) | 75 |

Filtering Unit

| | |
|---------------------------------|-----------|
| Cleaning system | Manual |
| Filter for oil/chips separation | TNT sheet |

Collection unit

| | | |
|-------------------|----|------------------|
| Powder capacity | lt | 75 |
| Liquid capacity | lt | 500 |
| Floating device | | Electric |
| Collection system | | Removable drawer |
| Discharge system | | Submersible pump |

Encumbrances

| | | |
|------------|----|--------------|
| Dimensions | cm | 182x101x134h |
| Weight | kg | 520 |

APPLICATIONS: Mechanical industry



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

FILTERING UNIT

Solids and chips are separated in an integrated container, whereas liquids are purified by means of a NW filter cloth.

COLLECTION UNIT

Possibility of cleaning the emptied tank with an adjustable high-pressure lance.

Independent 200l/min pump for re-injecting the emulsifier into the tank.