

# SKY 2000 – 2500 Coalescence filtration of oil mists

AIR FILTRATION SOLUTIONS



- ✓ Reduced energy consumption
- ✓ Quick and easy maintenance.
- ✓ Easy installation on the machine.
- ✓ Quick and easy filter replacement system.

## Suction unit

Voltage	V - Hz	400 - 50 ~ 3
Power	kW	0,75 - 1,1
Max air flow	m3/h	2000 - 2500
Construction		Painted steel
Noise level (EN ISO 3744)	dB(A)	65

## Filtering Unit

Surface - Diameter	cm <sup>2</sup> -mm	4.100/100.000 - 410
Cleaning system		Manual
Filter type		Multilayer or Cartridge

## Collection unit

Cyclon unit		Integrated
-------------	--	------------

## Encumbrances

Dimensions	cm	Ø59 x 59h
Weight	kg	46 - 50

## APPLICATIONS:



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# SKY 2000 – 2500 Coalescence filtration of oil mists

AIR FILTRATION SOLUTIONS

## **SUCTION UNIT**

The suction unit is a low-power, low-consumption, high airflow blower.

## **FILTERING UNIT**

Versatility of filtration: multi-layer filter (standard) or pleated cartridge with a high filtration surface area and a coalescing pre-filter

## **COLLECTION UNIT**

Vacuumed and filtered oils and emulsions settle on the wall of the vacuum cleaner and can be recovered through the discharge hose.

## **OPTIONALS**

- ✓ Installation kit with riser
- ✓ Installation kit with adjustable riser
- ✓ Wall mounting kit.
- ✓ Cyclone pre-filter kit.
- ✓ Adjustable column for floor fixing from 1.5 to 2.5 m.
- ✓ Absolute hepa filter h13 efficiency 99.95%