

# W3 AIR Compressed Air vacuum cleaner

## INDUSTRIAL VACUUM CLEANERS



- ✓ 100% steel construction.
- ✓ Large surface filter for fine dust with integrated manual cleaning system.
- ✓ Simultaneous vacuuming of dust, liquids and solids.
- ✓ Easy-to-empty detachable container.
- ✓ Compressed air supply via 2 Venturi units

### Suction unit

Max waterlift	mmH2O	5.000
Max air flow	m3/h	590 - 465
Suction inlet	mm	80
Construction		Painted steel
Noise level (EN ISO 3744)	dB(A)	79
Air supply	nlt/min (nm <sup>3</sup> /h)	2.500 - 1.530
Air supply pressure	bar	6
Air supply hose	mm	12

### Filtering Unit

Primary filter		Star
Surface - Diameter	cm <sup>2</sup> -mm	20.000 - 420
Material - Efficiency	IEC 60335-2-69	Polyester L
Cleaning system		Manual

### Collection unit

Capacity	lt	65 - 100
Collection system		Release container

### Encumbrances

Dimensions	cm	70x62x134h
Weight	kg	65

APPLICATIONS: Sandblasting



General housekeeping

Glass



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# W3 AIR Compressed Air vacuum cleaner

INDUSTRIAL VACUUM CLEANERS

## SUCTION UNIT

Suction is generated by two Venturi air vacuum units enclosed in a solid steel head containing sound-absorbing material. This minimises noise during operation.

## FILTERING UNIT

The polyester filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

## COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

## OPTIONALS

✓ Hepa absolute filter /h14